











<i>Standard</i>	Capacity	Internal dimensions		Door opening	Max. payload	Max. EUR pallets
20' Dry Cargo (DC) 	33 cbm	Lenght	5.898 mm	Width 2.340 mm Height 2.280 mm	28.160 kgs	11
40' Dry Cargo (DC) 	67 cbm	Lenght	12.035 mm	Width 2.340 mm Height 2.280 mm	26.760 kgs	25
40' High Cube Dry Cargo (HC DC) 	76 cbm	Lenght	12.035 mm	Width 2.340 mm Height 2.577 mm	26.750 kgs	25
45' High Cube Dry Cargo (HC DC) 	85 cbm	Lenght	13,556 mm	Width 2,340 mm Height 2.577 mm	28.280 kgs	27

<i>Reefer</i>	Capacity	Internal dimensions		Door opening	Max. payload	Max. EUR pallets
20' Reefer (RF) 	28 cbm	Lenght	5.451 mm	Width 2.286 mm Height 2.238 mm	27.490 kgs	10
40' High Cube Reefer (HC RF) 	67 cbm	Lenght	11,577 mm	Width 2,286 mm Height 2,535 mm	28,350 kgs	23

<i>Open Top</i>	Capacity	Internal dimensions		Top opening	Max. payload
20' Open Top (OT) 	32 cbm	Lenght	5.919 mm	Lenght 5.425 mm Width 2.223 mm	28.230 kgs
40' Open Top (OT) 	64 cbm	Lenght	12.029 mm	Lenght 11.909 mm Width 2.223 mm	26.580 kgs

<i>Flat Rack</i>	Max. height of cargo	Floor dimensions		Dimensions between stanchions	Max. payload
20' Flat Rack (FR) 	2.245 mm	Lenght	5.966 mm	Lenght 5.702 mm Width 2.200 mm	27.150 kgs
40' Flat Rack (FR) 	2.275 mm	Lenght	12.060 mm	Lenght 11.660 mm Width 2.200 mm	39.300 kgs